

BlocknZorbe™ Baffles

SPEC SHEET

- Easy to Hang
- No Fiberglass/Non-Fibrous
- Water Resistant
- Impact Resistant
- Lightweight
- Class A Fire Rated



Material:	Semi-Rigid Porous Expanded Polypropylene Acoustical Bead Foam					
Patterns:	Non Abrasive, Slightly Textured, Porous					
Features:	Easy to Hang, Rated for STC and NRC, Lightweight, Impact Resistant, Water Resistant, Bacteria & Fungi Resistant, Tack-able Surface					
Application:	Restaurants, Swimming Pools, Offices, Conference Rooms, Manufacturing Plants, Classrooms, Bars, Music Rooms, Universities, Hospitals, Medical Clinics, Houses of Worship, Theaters, Multi-Purpose Rooms, Municipal Facilities, Dog Kennels					
Thickness:	ו" & 2"					
Sizes:	24" x 48"					
Color:	Charcoal, White					
Fungal Growth:	Passes (no growth)					
Light Reflectance:	White: 90					
Flammability:	ASTM E84, Class A 1" : Flame Spread: 3 Smoke Developed: 84 2" : Flame Spread: 5 Smoke Developed: 113					
Installation:	Light Duty Chain (by other) & Corkscrews (included)					

Sabins per Baffle

Size	Test Mount	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	Sabins / Baffle
1" BlocknZorbe™ Baffle	16" Spacing	0.82	2.18	2.79	3.03	6.29	8.36	3.55
2" BlocknZorbe™ Baffle	16" Spacing	1.17	2.53	3.67	6.61	9.39	10.64	5.55





