

HEAT WAVE

Description

Heat Wave Thermal/Acoustic Insulation is a lightweight, foil faced, fire retardant blanket-type insulation with multiple uses. Heat Wave offers excellent thermal and acoustical performance and carries a Class-A fire rating.

Made from durable natural fibers, Heat Wave contains no fiberglass and does not itch or cause skin irritation. The fibers used to manufacture Heat Wave offer excellent sound absorption properties and every fiber is individually treated with an EPA registered anti-microbial agent that offers excellent protection from mold, mildew fungi, and pests as well as fire resistance.

Heat Wave's pure aluminum barrier reflects unwanted radiant heat and offers excellent protection from air currents, moisture, and vapors.

Uses

Use Heat Wave wherever unwanted heat or noise control is necessary.

Product Features

- **Excellent Noise Absorption**
- **Reduces Unwanted Heat**
- **No Itch or Skin Irritation**
- **Resists Microbial Growth**
- **Easy to Handle & Install**
- **Durable & Long-Lasting**

Physical Properties		
PROPERTIES	PERFORMANCE	TEST METHOD
Surface Burning Characteristics (Fire Hazard Classification)	Flame Spread 10 (Class 1) Smoke Developed 20 (Class 1)	ASTM E 84 UL 723
Zero Surface Burn Rate	Exceeds Standard (Less than 1/5 in./min.)	FMVSS 302
Facing	99% Pure Aluminum Reinforced Foil	
Foil Emissivity	.03	ASTM E 408
Foil Reflectivity	97%	ASTM E 408
Tensile Tear Strength	100 lbs.	
Pad Weight	3 oz./s.f.	

Thermal Technical Data	
Tested in accordance with ASTM C 177 and ASTM C 518	
POSITION	R-VALUE
UP	7.85
DOWN	16.39
HORIZONTAL	9.91
R-VALUE PER INCH	3.91
* The higher the R-Value, the greater the insulating power.	

Acoustical Performance							
Sound Absorption was tested in accordance with ASTM C 423 using a Type A mounting per ASTM E 795.							
PRODUCT	ABSORPTION COEFFICIENTS @ OCTAVE BAND FREQUENCIES (Hz)						
HEAT WAVE	125	250	500	1000	2000	4000	NRC
3/8" Pad	.12	.10	.23	.56	.81	.89	.45