

SECONDSKINAUDIO.COM 1.800.679.8511 SERVICE@SECONDSKINAUDIO.COM

Mela MuteTM Acoustic Foam Corner Bass Trap

SPEC SHEET

| Absorbs Low Frequencies |
|-------------------------|
| Super Lightweight |
| Easy to Install |


- Class A Fire Rated
- < Decorative & Paintable

Non-Fibrous & No Itch



| Material: | Open Cell Melamine Foam | | | | | |
|---------------------|---|--|--|--|--|--|
| Patterns: | Corner Bass Trap Triangular Prism, Porous, Semi-Rigid, Non-Fibrous | | | | | |
| Features: | Easy to Install, Absorbs Low Frequencies, Controls Echo & Reverb, Decorative, Lightweight, Class A Fire Rated, Paintable, Non-Fibrous, Non-Toxic | | | | | |
| Application: | Recording Studios, Broadcast Studios, Offices, Conference Rooms, Restaurants, Music Rooms, Universities, Hospitals, Schools, Houses of Worship, Theaters, Multi- Purpose Rooms, Government & Municipal Facilities | | | | | |
| Height: | 24" & 48" | | | | | |
| Dimensions: | 12" x 12" (outer edges) Nominal 17" (inner edge) | | | | | |
| Weight | 24": 1lbs 48": 2lbs | | | | | |
| Color: | White, Light Grey, Dark Grey | | | | | |
| Temperature Rating: | -40°F to 350°F | | | | | |
| Flammability: | ASTM E84, Class A Flame Spread: 10 Smoke Developed: 50 | | | | | |
| Installation: | P329 Spray Adhesive or Construction Adhesive | | | | | |

| Sabins per Unit | | | | | | | | | | |
|---------------------------------|------------|--------|--------|--------|---------|---------|---------|---------------|--|--|
| Size | Test Mount | 125 Hz | 250 Hz | 500 Hz | 1000 Hz | 2000 Hz | 4000 Hz | Sabins / Unit | | |
| 48" Mela Mute™ Corner Bass Trap | A-Mount | 3.60 | 9.70 | 9.50 | 8.25 | 6.80 | 5.15 | 8.60 | | |







to order this product visit: Mela Mute™ Acoustic Foam Corner Bass Trap