

POLYZORBE™ POLYESTER HEXAGON ACOUSTIC PANELS

SPEC SHEET

- Decorative and Colorful
- Controls Echo & Reverb
- No Formaldehyde or Irritants
- Class A Fire Rated
- Easy to Install



Material:	Polyester (60% Recycled)						
Patterns:	Fibrous, Semi-Rigid						
Features:	Decorative, Lightweight, Tackable Surface, No Irritants, Color Variety						
Application:	Homes, Apartments, Recording Studios, Hotels, Conference Rooms, Offices, Music Rooms, Houses of Worship, Community Centers, Hospitals, Auditoriums, Malls, Retail Stores, Schools, Restaurants, Bars						
Thickness:	1/2"						
Thickness: Sizes:	1/2" 10-3/8" x 12" (nominal 1 sq ft), Call for custom shapes and sizes						
	· ·						
Sizes:	10-3/8" x 12" (nominal 1 sq ft), Call for custom shapes and sizes						



Sound Absorption / Noise Reduction Coefficient										
Size	Mount	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	NRC		
1/2" Thick	Wall Mounted (Type A)	0.01	0.07	0.26	0.54	0.78	0.94	0.40		
1/2" Thick	Wall Mounted with 3/4" Air Space (Type D-20)	0.09	0.14	0.39	0.78	0.97	1.01	0.55		
1/2" Thick	Wall Mounted with 1-1/2" Air Space (Type D-40)	0.09	0.25	0.68	0.94	1.00	0.86	0.70		

Color Options Orange Brown Red Grey Black Silver Beige Tan White Blue Purple Green

