

THE STOMP MAT

SPEC SHEET

- High Density Floor Isolation Mat
- Use Underneath Treadmills,
 Exercise Equipment and More
- Reduce Impact Noise
- Can Be Used as Finished Floor
- Flame & Chemical Resistant
- Easy to Clean



Material:	100% Recycled Rubber (Car Tires)
Patterns:	Smooth, Dense
Features:	Extremely Durable, Absorbs Shocks and Isolates Acoustical Vibrations, Easy to Clean, Non-Slip
Application:	Isolation mats for equipment, drum mats, treadmill mats, golf simulators, home gyms, commercial gyms, warehouses, military bases
Thickness:	½" or ½"
Weight:	30 lbs (1/4" thick), 60 lbs (1/2" thick)
Sizes:	48" x 72", Call for custom sizes or rolls
Color:	Black
Flammability:	Passes ASTM D2859
Installation:	Roll out or lay on floor

Spec Sheet			
Item	Test Standard	Result	
Tensile Strength	ASTM D-412	266 PSI	
Density	ASTM D-3676	65 lbs / cubic foot	
Tear Resistance	ASTM D-413	155%	
Hardness	ASTM D-2240	Shore A 65 +/- 5	
Compression Set	ASTM D-395	-4.90%	
Slip Resistance		Pass	
Coefficient to Friction	ASTM D-2047	> 0.8	
Flammability	ASTM D-2859	Pass	
Resistance to Chemicals	F-925-02	Resistant to most acids and chlorine	
VOC Emissions	ASTM DS-116	0.5 mg/m2 or less	
Sound Transmission Class	ASTM E-90	STC 59	
Impact Insulation Class	ASTM E-492	IIC 69	
Delta Impact Insulation Class	ASTM E-2179	Δ IIC 34	



