

UNDERBLOCK HD

SPEC SHEET

Increases IIC	ratings		
 100% recycled rubber Lay flooring tile directly on top 			
			ASTM tested
🗸 Easy to insta	11	Billion and	
Material:	Recycled Rubber (100%)		
Patterns:	Flat, Semi-Smooth		
Features:	Damps Vibrations and Blocks Airborne Noise, 100% Waterproof Vapor Barrier, Excellent Under Hardwood, Tile, or Carpet, ASTM Testing		
Application:	Multi-family condos, multi-family apartments, multi-family housing, commercial buildings, hotels, offices, community centers, hospitals, auditoriums, malls, retail stores		
Thickness:	3/8", 1/2"		
Sizes:	4' x 25' (3/8"), 4' x 20' (1/2")		
Color:	Black		
Flammability:	ASTM E-84, Class C Flame Spread: 83 Smoke Developed: 315		
Installation:	Roll out on subfloor		



Technical Data	Standards	Value
Hardness	ASTM-D412	55/65 (Shore A)
Puncture Resistance	Factory Tested Weight: 120psi Time: 1 Week	<0.3 mm
Abrasion Resistance	ASTM-D3389	0.41 mg
Dimensional Stability	Factory Tested -15 C to 30 C	100 %
Flame Propagation Index	ULCS-101.2 ASTM-E84	83
Smoke Emission Index	ULCS-101.2 ASTM-E84	315
Chemical Resistance	Laboratory Tested Javel water (5%) HCI SOLN (26%)	100 %
Electrical Conduction	ASTM-D2565	10 ⁷ Ohm
Absorption	Factory Tested	0 %

6" or 8" CONCRETE SLAB

1. Finished Floor (Ceramic, marble, LVT, LVP, etc.)



3. 6" or 8" concrete slab



UNDERBLOCK HD TEST RESULTS WITH 6" OR 8" CONCRETE SLAB (NO DROP CEILING)

Finished tile floor Thin set kerolastic UnderBlock HD 3/8" DA5 Duro Adhesive	ІІС	STC
6" Concrete Slab	60	60
8" Concrete Slab	63	63
Finished tile floor Thin set kerolastic UnderBlock HD 1/2" DA5 Duro Adhesiye	IIC	STC
6" Concrete Slab	61	60
8" Concrete Slab	64	64

6" or 8" CONCRETE SLAB

Finished Floor (1/2" wooden laths)
 UnderBlock HD
 6" or 8" concrete slab



UNDERBLOCK HD TEST RESULTS WITH 6" OR 8" CONCRETE SLAB (NO DROP CEILING)

IIC	STC
58	60
67	64
IIC	STC
65	61
68	66
	58 67 IIC 65



to order this product visit: secondskinaudio.com/soundproofing/underblockhd